

THE KAIVAC® 2150

EQUIPMENT SPECIFICATIONS

DESCRIPTION

Water Tank	21 Gallons (79,5 l)
Spray Time	21 Minutes
Flow Rate	1 GPM (3,7785 l/min)
Pressure (at gun)	500 psi (34,5 bars)
Vac Tank	19 Gallons (72 l)
See-Through Vac Tank	Yes
Dump Hose	42" (106,7 cm) Long
Toilet Dumping	Yes
Vac Tank Cleanout	100%
Method of Dumping	Drain Hose
Vac Motor Lift	113" (287 cm)
Vac CFM	107 cfm (3030 l/min)
HEPA Blow Feature	300 mph (482,7 km/h)
DVD Player	Optional

CHEMICAL

Molded-In Chemical Holder	Gallon (2), Quart (2)
Chemical Switching	Dual/Quick Change
Safety Cap System	Yes
Metering Tip Settings	5 Settings

ELECTRICAL

(Safety Certified by Entela to ANSI/UL #1017)

Volts (U.S.)	110 Volt - 60 Hz
Volts (Universal)	100-240V; 50-60Hz
Amps Total	14.5 amp
GFCI	Yes

CORDS AND HOSES

Vac Hose	75 ft. (22,9 m)
Spray Line	75 ft. (22,9 m)
Quick-Connect Gun	Yes
Electric Cord	50 ft. (15 m)
Blow Hose	33 ft. (10 m)

BODY

Rotational Mold	Yes
Weight	159 lb. (72.1 kg)
Size (H x L x W)	51" x 32" x 24" (129,5 x 81,3 x 61,0 cm)
Flat-free Non-marking Pneumatic Tires	(2) 10" (25,4 cm)
Casters	(2) 5" (12,7 cm), locking (2)
Stair Climbing Wheels	Yes
Handle	Molded-In
Tray	Molded-In
Parking Brake	Yes

TOOLS INCLUDED

Vac Wand Aluminum	1-Piece
14 Inch Squeegee Head	Yes
Blow Nozzle	Yes
Training Materials	Video and Placard
KaiBrush	Yes
Window Squeegee	Yes
Metering Tip Kit	Yes
KaiDrain	Yes
15 Gallon Tote Bag	Yes

WARRANTY WITH KAIVAC CHEMICAL USAGE

Body	10 Years
Parts	3 Years
Labor	1 Year



kaivac cleaning systems™
Complete Cleaning For Healthy Results™